

# COUPLING LOCK PIN AND WHIPCHECK SELECTION GUIDE

## DOUBLE SAFEGUARD BY USING LOCK PINS AND WHIPCHECKS

														
	BRASS THREADED COUPLING	BLAST HOSE QUICK COUPLING 40-60mm OD Hose	BLAST HOSE QUICK COUPLING 60mm OD Hose	NYLON THREADED COUPLING	NYLON HOSE QUICK COUPLING	THREADED AIRLINE COUPLING	HOSE TAIL AIRLINE COUPLING	SCREW TYPE BULL HOSE FITTING	AIR AND BLAST HOSE 1/2" to 1" OD	AIR AND BLAST HOSE 1" to 1 1/2" OD	AIR AND BLAST HOSE 1 1/2" to 2" OD	AIR AND BLAST HOSE 2" to 2 1/2" OD	AIR AND BLAST HOSE 2 1/2" to 3" OD	AIR AND BLAST HOSE 3" to 3 1/2" OD
HFCLP1 	✓	✓	✓	✗	✗	✓	✓	*						
HFCLP2 	✓	✓	✓	✗	✗	✓	✓	*						
HFCLP3 	✗	✗	✓	✓	✓	✗	✗	*	<i>Relevant coupling lock pin is dependent on selected coupling</i>					
HFCLP4 	✓	✓	✗	✗	✗	✓	✓	*						
HFSCA5 									✗	✓	✗	✗	✗	✗
HFSCA6 									✗	✗	✓	✗	✗	✗
HFSCA7 									✗	✗	✗	✓	✗	✗
HFSCA8 									✗	✗	✗	✗	✓	✗
HFSCA1 									✓	✓	✓	✓	✗	✗
HFSCA2 									✗	✗	✗	✗	✓	✓
HFSCA3 									✓	✓	✓	✓	✓	✓

*Relevant whipcheck is dependent on selected hose*

\*As screw type fittings cannot be protected with lock pins, Blast-One recommends using a hose restraint stocking for this type of coupling.